## PREVENTATIVE MAINTENANCE POLICIES / SCHEDULE

## **GUIDELINES**

These recommendations are based on normal operating conditions and correspond with the O&M manual.

Certain situations or circumstances may require increased frequency. See Notes section for more information on each maintenance item.

ACTIVE DEVICES												
EON	Millenium HX	WRO 300 H	WRO 300	700 Series								
Senter ECN	The state of the s	© MARKETON	S ON MARION	10000								

#	MAINTENANCE ITEM	FREQ.	TIME								
1.	1. COMPLETE LOG SHEET		-	D	-	D	-	D	-	D	-
2.	2. PRE-FILTER REPLACEMENT		0.18	1M	0.18	1M	0.18	1M	0.18	1M	0.18
3.	3. CARBON FILTER REPLACEMENT		0.25	3M	0.25	3M	0.25	3M	0.25	3M	0.25
4.	. ENDOTOXIN FILTER REPLACEMENT		0.18	-	-	-	-	6M	0.18	6M	0.18
5.	5. TOTAL CHLORINE LEVEL TEST		-	D	-	D	-	D	-	D	-
6.	6. HARDNESS LEVEL TEST		-	D	-	D	-	D	-	D	-
7.	7. AAMI WATER TEST		-	12M	-	12M	-	12M	-	12M	-
8.	8. BACTERIA TEST		-	1M	-	1M	-	1M	-	1M	-
9.	. LAL TEST		-	1M	-	1M	-	1M	-	1M	-
10.	RO CLEAN, CHEMICAL	AR	1.5	AR	2.0	AR	2.0	AR	2.0	3M	3.0
11.	RO DISINFECT, CHEMICAL	-	-	-	-	-	-	1W	1.5	3M	2.0
12.	RO DISINFECT, HEAT	1W	1.0	1W	2.5	1W	1.0	-	-	-	-
13.	RO PRESERVE, CHEMICAL	LTS	-								
14.	MEMBRANE REPLACEMENT	-	-	-	-	-	-	-	-	-	-
15.	. AIR FILTER REPLACEMENT		-	-	-	12M	0.18	12M	0.18	-	-
16.	6. PROTECTIVE EARTH TESTING		0.18	-	-	3M	0.18	3M	0.18	-	-
17.	7. PRODUCT WATER FLOW TEST		-	-	-	12M	0.25	12M	0.25	6M	0.25
18.	3. CONDUCTIVITY TEST		0.25	3M	0.25	3M	0.25	3M	0.25	3M	0.25
19.	OPERATING PANEL TEST	-	-	-	-	12M	0.18	12M	0.18	-	-
20.	CHEMICAL IN-TAKE O-RING TEST	-	-	-	-	12M	0.18	12M	0.18	-	-
21.	BATTERY REPLACEMENT	36M	0.18	-	-	12M	0.18	12M	0.18	-	-
22.	INSPECT HOSE AND CONNECTION PORTS	6M	0.25	3M	0.25	3M	0.25	3M	0.25	3M	0.25
23.	CLEAN FAN/SCREEN	-	-	-	-	-	-	-	-	6M	0.18
24.	4. LUBRICATE MOTOR		-	-	-	-	-	-	-	12M	0.18
25.	25. PRESSURE SWITCH TEST		-	-	-	-	-	-	-	12M	0.18
26.	26. REPLACE VALVE INTERNALS		1.0	-	-	-	-	-	-	-	-

Time shown as hours, estimate per device under normal conditions; changes based on feed water, water temperature, water quality, materials, and personnel. Chemical process on the EON and WRO 300 units is semi-automated. Heat disinfection process on EON, Millenium HX and WRO 300 H is designed to be automated.

## PREVENTATIVE MAINTENANCE POLICIES / SCHEDULE NOTES

## **NOTES**

- 1. A log sheet should be completed every day or every time the device is used.
- 2. The pre-filter may need to be changed more often based on incoming water quality and system usage.
- Carbon filter or carbon tanks may need to be exchanged more often based on incoming chlorine levels and system usage.
- The endotoxin (final) filter is not standard of every system. It may need to be changed more often based on bacteria testing/usage.
- Total Chlorine testing should be completed prior to every patient treatment.
- Hardness testing may not be applicable in all areas. If a softening device is not used, then testing is not required.
- AAMI water testing to ensure the RO is in compliance. More often may be beneficial.
- Bacteria testing to ensure the RO is in compliance. More often may be beneficial.
- LAL testing to ensure the RO is in compliance. More often may be beneficial.
- RO cleaning should be done based on RO performance. As Required (AR) time includes both low/high pH cleaner, except for EON and Millenium HX.
- 11. RO disinfecting should be done after a chemical cleaning and/or as required based on RO performance.
- Heat RO disinfecting should be completed as least once a week, but more often is acceptable. Times vary based on feed water temperature and on schedules. Time not caluculated in Yearly PM hours due to automation.
- Preserving an RO machine is based on Long Term Storage (LTS) requirements.
- Replacement based on RO performance. Reliable incoming water quality along with RO clean/disinfect are ways to prolong membrane life. 14.
- Routine replacement. 15.
- Routine testing. 16.
- Routine testing. 17
- 18 Routine testing.
- 19. Routine testing.
- Routine testing. 20.
- Routine replacement. 21.
- Routine inspection. 22.
- 23. Routine cleaning.
- 24. Routine action as required.
- Routine testing. 25.
- Routine replacement.

EON™ and Millenium HX™ are trademarks of Mar Cor Purification Inc., A Cantel Medical Company,

Visit mcpur.com for more information or call 1-800-633-3080

