



# CWP 100 H

Reverse Osmosis System  
5,000 to 13,000 GPD

**510(k) Medical Device**

## GENERAL INFORMATION

The CWP 100 H offers cost-effective, consistent delivery of water meeting or exceeding ANSI/AAMI 13959 water standards for dialysis.

The semi-automated heat disinfection of the distribution loop and the automated chemical disinfection of the RO and membranes simply and easily reduce biofilm development and minimizes levels of endotoxin, fungi, yeast and other microbial contaminants.

Greater cost-effectiveness is ensured through system efficiency and labor savings. The CWP represents a simple, convenient, and effective disinfection strategy. Advanced electronics and top quality components also ensure quiet, reliable, and safe operation.

## STANDARD FEATURES

- Hot water loop disinfection
- Medical-grade Wirsbo-cleanPEX® distribution system
- Direct feed operation
- Semi-automated disinfection of the loop and RO membrane
- Integrated end-to-end heat with the Phoenix® Hemodialysis System
- Monitoring software for documentation and verification of disinfection procedures
- ETL certified



## OPTIONAL ITEMS

We offer a complete line of components and accessories, including:

- Blending Valves and Booster Pumps
- Multi-Media Filters
- Water Softeners
- Carbon Adsorption
- Hardness and Total Chlorine Test Kits
- AAMI Water Analysis
- Chemical Disinfectants

# CWP 100 H Specifications

Product Water - Minimum capacity at 20 °C and at a pure water outlet pressure of 29 psi (200 kPa)

Output	Model	101 H	102 H	104 H	106 H
	Part Number	W3T579303	W3T579302	W3T579304	W3T579300
	Product Water in gallons/min (l/min)	3.4 (13)	5.3 (20)	7.7 (29)	9.3 (35)
Quality	Depends on inlet water quality. The system is designed to utilize drinking water that meets the standards of the Safe Drinking Water Act, 40 CFR. Additional pretreatment of inlet water is required. A properly maintained system using inlet water meeting SDWA can obtain the following rejection rates: Total dissolved salts > 95% • Bacteria (CFU) & endotoxins > 99% • Water conversion factor 67%				

## Water Supply

Input	Model	101 H	102 H	104 H	106 H
	Min Input flow in gallons/min (l/min)	5.3 (20)	7.9 (30)	13.2 (50)	15.9 (60)
	Min Input pressure in psi (kPa)	15 (100)	15 (100)	36 (250)	51 (300)
	Max Input pressure in psi (kPa)	73 (500)	73 (500)	73 (500)	73 (500)
Temperature	+5 °C to +25 °C* *(Maximum +20 °C if peracetic acid is used for disinfection)				

## Drain Requirements

Peak Flow (Rinse)	Model	101 H	102 H	104 H	106 H
	Required capacity in gallons/min (l/min)	5.3 (20)	7.9 (30)	13.2 (50)	15.9 (60)
	Note: Maximum flow occurs during flushing				

## Reverse Osmosis Membranes

Material	Modified polyamide, thin film composite
Configuration	Spiral wound
pH-Tolerance	2-11

## Power Supply

Main Voltage	120/208 V, 60 Hz, 3-phase (5 wires)
Power rating	RO-unit 101-104: 1.8 kW; RO-unit 106: 2.5 kW; Heating unit 101-106: 9.0 kW
Fuse	16 AT + 32 AT, 16 (slow blow) or 40 AT (slow blow) one supply

## CWP 100 H Dimensions

Model	101 H	102 H	104H	106 H
Depth	26.4 in (670 mm)	26.4 in (670 mm)	26.4 in (670 mm)	26.4 in (670 mm)
Width	68 in (1720 mm)	75 in (1910 mm)	83 in (2100 mm)	83 in (2100 mm)
Height	79.1 in (2010 mm)	79.1 in (2010 mm)	79.1 in (2010 mm)	79.1 in (2010 mm)

## CWP 100 H Weight

Model	101 H	102 H	104 H	106 H
Unit	1014 lbs (460 kg)	1113 lbs (505 kg)	1224 lbs (555 kg)	1290 lbs (585 kg)
Unit w/ Packaging	1466 lbs (665 kg)	1664 lbs (755 kg)	1819 lbs (825 kg)	1885 lbs (855 kg)
Unit in Operations	1709 lbs (775 kg)	1995 lbs (905 kg)	2128 lbs (965 kg)	2216 lbs (1005 kg)

Note: 20 inches (500mm) extra space is required on both sides of the unit.



Visit [mcpur.com](http://mcpur.com) for more information or call 1-800-633-3080

Mar Cor is a trademark of Evoqua Water Technologies LLC, its subsidiaries or affiliates in some countries.

Phoenix is a trademark of Gambio Lundia AB. Wisbo-cleanPEX is a trademark of Uponor Wirsbo AB.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.