

700 SERIES PORTABLE

Reverse Osmosis System
650 to 2600 ml/min

510(k) Medical Device

STANDARD FEATURES

- Specially designed for quiet operation.
- Advanced performance monitoring includes percent rejection and a digital display of product water total dissolved solids as mg/L. For added safety, an audible alarm with adjustable set points is incorporated into the TDS monitor. The monitoring and instrumentation meets the standards recommended by the Association for the Advancement of Medical Instrumentation (AAMI).
- Panel-mounted pressure gauges continuously display important prefilter, pump, and product pressures.
- Space-efficient design for easy portability.
- Chemically compatible with 1% Minncare® HD Disinfectant solution.
- Stainless steel RO pump and pressure vessels are used for maximum strength, reliability, and longevity.
- Thin film RO membranes for high quality & long life.
- Incoming water solenoid allows for easy changing of the pre-filter element and system cleaning/disinfecting without disconnecting the incoming water supply.
- Product water recirculation returns the excess product water into the feed stream, which reduces stress on the RO membranes, conserves water, inhibits bacterial growth, and lowers operating costs.
- Easy to expand design allows for additional membranes to be added, increasing the capacity up to 2600 ml/min at 77°F (25°C); (see operating parameters). We strongly suggests operating only one dialysis machine per 700 Series RO because the life of the pump and membranes will be significantly decreased.
- FDA registered manufacturer meets stringent medical device requirements.
- Listed as certified by CSA to Canadian and U.S. medical electrical standards. The 700 Series RO has been tested to and demonstrates compliance with CAN/CSA C22.2 No. 601.1-M90 (Safety of Medical Electrical Equipment, Part I; General Requirements for Safety) and UL STD 2601-1 (Safety of Medical Electrical Equipment Part I; General Requirements for Safety).



OPTIONAL FEATURES

We offer a complete line of system components and accessories including:

- Replacement Prefilters
- 36" (91 cm) Tall Cabinet
- Pretreatment Cart
- AAMI Water Analysis
- Disinfectant Tank
- Hardness & Total Chlorine Test Kits
- Carbon Tanks, Sediment Filters & Water Softeners
- High and Low pH Cleaners

700 Series RO Specifications

Model	701	702	703	703	703 (Cold) ¹
Production Rate					
ml/min	656	1312	1968	2624	2060
L/hr	39	79	118	157	124
Gallons/hr	10.4	20.8	31.2	41.6	32.7
Recovery Rate	17%	29%	38%	45%	45%
Dry Rate					
lbs	55	73	79	85	90
kg	25	33	36	39	41
Power Required	115/230 V, 60/50 Hz, 8/5 amps				
Dimensions	(Short Cabinet) (Tall Cabinet)	Depth - 14" (36 cm) Height - 26" (66 cm) Width - 18" (46 cm) Depth - 14" (36 cm) Height - 36" (92 cm) Width - 18" (46 cm)			

NOTE: Initial product flow rate based upon membrane manufacturers' specifications of pretreated feed water, 200 PSI (14 bars) applied pressure, 77°F (25°C) incoming water temperature, 1,000 ppm (mg/L) NaCl, 10% recovery and 1 PSI (0.07 bars) product pressure. Membrane flux may vary ± 10%. Product water flow rates specified @ 40°F (5°C). Operation of the 704 (Cold) Series RO unit at temperatures above 55°F (13°C) will result in shortened membrane life.

¹Cold water option available in tall cabinet only.

Feedwater Requirements

pH	Operating: 5.5-10.5	Cleaning: 2-11
pH with Chloramines	Operating: 5.5-8.5	Cleaning: 2-11
Temperature	35-90°F (1.7-32°C)	
Water production decreases approximately 1.5% per 1°F (3% per 1°C) incoming water temperature drop.		
Inlet Pressure (Dynamic)	Minimum: 30 PSI (2 bars)	Maximum: 100 PSI (7 bars)
Inlet Water Flow	Minimum: 2 gpm (7.6 L/m)	
Total Hardness	100 ppm (mg/L) (pH dependent)	
Silt Density Index (SDI)	<5	

Note: Detailed analysis of the feed water will dictate the components, if any, needed in pre- or post-treatment of the 700 Series RO unit. This will help assure a constant supply of water, meeting AAMI Dialysis Water Quality Standards.



Visit mcpur.com for more information or call 1-800-633-3080

Minnicare is a trademark of Medivators Inc. used under license.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2024 Evoqua Water Technologies LLC Subject to change without notice P/N:W3T577375 Rev.I