

MINNCLEAN®

Reverse Osmosis Membrane Cleaners

MINNCLEAN® AC CLEANER

For use on thin film composite (polyamide) reverse osmosis membrane systems. Especially formulated to remove mineral scale (calcium carbonate) and metal hydroxides from the membrane surface. Minnclean AC is an acidic (low pH) membrane cleaner.

MINNCLEAN® TF CLEANER

For use on thin film composite (polyamide) reverse osmosis membrane systems. Especially formulated to remove organic foulants such as grease, grime and biological matter from the membrane surface. Minnclean TF is an alkaline (high pH) membrane cleaner.

SPECIFICATIONS

Compounds	Acidic Powder (AC), Alkaline Powder (TF)
Normal Cleaning Mix Ratio	1 pound cleaner per 15 gallons RO water
pH of Solution	2.0 to 2.4 (AC), 11.2 to 11.4 (TF)
Foam Level	Moderate
Cloud Point	None
Rinsability	Good
Storage	Store sealed container in a cool dry place



Minnclean AC and Minnclean TF in the United States and Canada

Part Number	Description	Quantity
W2T912011	Minnclean AC Reverse Osmosis Membrane Cleaner	10 pound container
W2T914432	Minnclean AC Reverse Osmosis Membrane Cleaner	2 ten pound containers
W2T912012	Minnclean TF Reverse Osmosis Membrane Cleaner	10 pound container
W2T914433	Minnclean TF Reverse Osmosis Membrane Cleaner	2 ten pound containers

MINNCLEAN® AC

REVERSE OSMOSIS MEMBRANE CLEANER — ACID

For removing mineral scale in membrane applications.

MINNCLEAN® TF

REVERSE OSMOSIS MEMBRANE CLEANER — ALKALINE

For removing oil, grease, biological matter and grime on thin film composite membrane surfaces.

DIRECTIONS

1. Drain as much water from the system as possible.
2. Attach feed water, product water and waste discharge lines to a 30 gallon or larger tank and fill unit and tank with good quality water.
3. Use 1 pound of Minnclean AC or Minnclean TF for every 15 gallons of water in the system. Stir well to aid dissolution. For best results, water temperature should be 95-105°F (35-40°C).
4. Recirculate cleaning solution in forward mode at minimum possible pressure for 30 minutes.
5. Discharge cleaning solution to drain, drain system, clean tank and fill with clean water. Rinse for 15 minutes, adding water as needed.
6. After rinsing, return system to service and discard product water for at least 30 minutes after start up.
7. Repeat cleaning cycle if flux has not been returned to expected value.

NOTICE: It is the responsibility of the user to observe any limitations and/or parameters of chemical compatibility placed on the membranes by the manufacturer.

WARNING:

May cause burns. Harmful if swallowed.

(AC) Contains Sulfamic Acid; (TF) Contains Disodium Trioxosilicate

Prevent contact with skin, eyes and avoid contamination of clothing. Do not take internally. Prevent breathing dust. Use approved goggles and rubber gloves when handling.

For chemical emergency, spill, leak, fire, exposure or accident, call CHEMTREC +1 703 527 3887. Consult material safety data sheet for additional information. For industrial use only.

DO NOT MIX WITH CHLORINATED SOLUTIONS OR COMPOUNDS.



Visit mcpur.com for more information or call 1-800-633-3080

MINNCLEAN is a trademark of Evoqua Water Technologies, LLC., its subsidiaries, and affiliates in some countries.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2024 Evoqua Water Technologies LLC Subject to change without notice P/N:W3T576387 Rev.C